

Ceiling Speaker System



# Ceiling & Projector Audio Enhancement

Introducing the Astronaut XL from the renowned Astronaut ceiling speaker series. It's twice as loud as the CL and produces a deeper, full-range audio experience. From standard classrooms, to cafetoriums, to computer labs, the XL's proven Astronaut technology ensures every listener hears voice and multimedia as intended with incredible speech intelligibility. And, as promised by all Cetacea products, the XL delivers unparalleled price performance.

# **Product Features**

- 60 watts total system power
- Up to 1,500 sq. ft. soundfield coverage with 12' ceilings
- 360° omni-directional acoustics for group listening applications
- Pre-equalized for superior speech intelligibility
- 3-channel mixer supports projectors, microphones, DVD's, smartphones, computers, and whiteboards
- Simple below the ceiling installation with included bracket
- ENERGY STAR® power and internationally certified

# **System Includes**

- · Astronaut XL Speaker
- · Ceiling Mount Kit
- Power Supply






Astronaut series products are covered by multiple pantents that are registered or under license to Cetacea Sound Corp.






# **Simple and Secure Installation**


The included bracket allows for quick and easy mounting to the ceiling. The Astronaut can be mounted almost anywhere on the ceiling but for the best result, mount it close to the audience.



# **Ceiling Mount Kit**

Astronaut series speakers come standard with a ceiling mount kit for simple installation to ceiling tiles or hard-surfaced ceilings. Eye bolt prevents unwanted removal of the Astronaut from below the ceiling.





- 1 Mounting Bracket
- 3 Bracket Bolts (4)
- 2 Ceiling Plate
- 4 Security Eye Bolt

# **Ordering Information**

Choose from 3 Astronaut XL packages.

SKU# ASTXLW1 Astronaut XL speaker, ceiling mount kit, power supply (6')
SKU# ASTXLD1 Astronaut XL speaker, ceiling mount kit, power supply (12')

SKU# ASTXLR1 Astronaut XL speaker, ceiling mount kit, power supply (6'), power extension cable (30')

# Options

SKU# AB-163RS Inline Volume Control

SKU# AB-145 50'Stereo Speaker Cable, 3.5mm, M-M SKU# AB-167 20'DC power extension cable

SKU# AB-124 30' DC power extension cable

# **System Specifications**

#### Electrical

### **Signal Connections**

3 input jacks, 3.5mm, mono-stereo with auto detection and mix-down

# Input Impedance

62k ohms

### Amplifier Power/Requirements

60W total system power 15 VDC / 15W

#### **Power Supply**

Part # FW-PSE1515W or FW-PSE1515D Switch mode, low noise, high efficiency Voltage input: 100-240V, 50/60 Hz Voltage output: 15 VDC

- · 85% efficient
- Fuse and over-temp protection (80° C)
- Regulation +/- 5%
- Ripple and noise less than 1%
- · Overload and over-voltage protection
- Short circuit protection with auto-recovery
- CEC Level VI compliant
- < 0.1W stand-by power consumption
- Approvals: UL, cUL, TUV, PSE, CSA, CCC, BEAB

#### Acoustics

- Omni-directional horn with ceiling acoustic coupling (patented)
- Magnetically shielded custom Audiophile® transducer (patented)
- · Custom tuned cabinet (patent pending)
- · Custom tuned port

# Performance

# **Frequency Response**

70-15 kHz@-3 dB

# Signal to Noise Ratio

 $> 90 \, dB$ 

### Loudness

94 dB

### **Port Tuning**

90 Hz

#### Mechanical

#### **Astronaut Dimensions**

Diameter - 8" Height - 3.5" Weight: 1 lb. 10 ounces (.7 kg)

# **Power Supply Dimensions**

4.33" x 2.07"x 1.44" 8 ounces

### **Power Cord**

- Standard CEC certified wallwort power supply - 6' reach with tuning fork barrel connector
- Optional CEC certified desktop style power supply with removal AC cord, 12'reach

# Compliance

UL, cUL, CE, ENERGY STAR®, CEC VI

### Warranty

Full two years on all components

